



Power Supply

Four Output DC Regulated Power Supply

OPS4330

- Four channels of DC regulated output; two adjustable and two fixed channels.
- Four LED displays for displaying output voltage and current values of each channel.
- Two adjustable outputs with constant voltage and current; automatic status change.
- Adjustable current limiter; overload and short circuit protection.
- Two channels of output voltage can be in series or parallel; can track voltage and current (in parallel) with master power.

| Model | | OPS4330 | |
|----------------------------|------------------|-------------------------------|----------|
| Specification | Output Voltage | Master | 0 ~ 30 V |
| | | Slave | |
| | | Fix | 5 V |
| | Output Current | Master | 0 ~ 3 A |
| Slave | | | |
| Fix | | 3 A | 3 A |
| Load Effect | CV | 5 x 10 ⁻⁴ + 2 mV | |
| | CC | 20 mA | |
| Source Effect | CV | 1 x 10 ⁻⁴ + 0.5 mV | |
| | CC | 1 x 10 ⁻³ + 5 mA | |
| Ripple and Noise | CV | 1 mVrms | |
| | CC | 1 mArms | |
| | Display Accuracy | ± 1% + 2 word | |
| | Work Temperature | 0 ~ 40 °c | |
| | MTBF Reliability | ≥2000h | |
| | Power Voltage | AC 220 V ± 10%; 50 Hz ± 5% | |
| Mechanical Characteristics | Dimensions | 160 mm x 270 mm x 320 mm | |
| | Weight | 9 kg approx. | |

Options

| | |
|------------|--------------------------------|
| OPS4330-A1 | Adjustable Current Limit Point |
|------------|--------------------------------|