



Power Supply Triple Output DC Regulated Power Supply

OPS3530

- Three channels output, two adjustable, one fixed.
- Four LED indicate two channels of output voltage and current value of each.
- Two adjustable output has constant voltage and current and auto-switched.
- Overload, short circuit, adjustable current limit protection.
- Two channels of output voltage can be in series or parallel arbitrarily, and track voltage and current with master power.

Model		OPS3530	
Specification	Output Voltage	Master	0 ~ 30 V
		Slave	
		Fix	5 V
	Output Current	Master	0 ~ 5 A
		Slave	
		Fix	5 A
Load Effect	CV	5 x 10 ⁻⁴ + 2 mV	
	CC	20 mA	
Source Effect	CV	1 x 10 ⁻⁴ + 0.5 mV	
	CC	1 x 10 ⁻³ + 5 mA	
Ripple and Noise	CV	1 mVrms	
	CC	1 mArms	
	Display Accuracy	± 1% + 2 word	
	Work Temperature	0 ~ 40 °c	
	MTBF Reliability	≥2000h	
	Power Voltage	AC 220 V ± 10%; 50 Hz ± 5%	
Mechanical Characteristics	Dimensions	160 mm x 270 mm x 320 mm	
	Weight	9 kg approx.	

Options

OPS3530-A1	Adjustable Current Limit Point
------------	--------------------------------