



## Optical Power Meter

### OHOP6000 Series

- 850/1300/1310/1490/1550/1625 nm calibrated wavelengths.
- SM or MM applications.
- Wide measurement range, high resolution.
- 2.5 mm universal connector.
- Auto power off (can be disabled).

Model	OHOP6006	OHOP6026
Display Range	1310/1490/1550/1625 nm: -70 ~ +10 dBm 850/1300 nm: -60 ~ +6 dBm	1310/1490/1550/1625 nm: -50 ~ +26 dBm 850/1300 nm: -40 ~ +26 dBm
Accuracy	± 0.2 dB	
Calibrated Wavelengths	850 nm/1300 nm/1310 nm/1490 nm/1550/nm/1625 nm	
Display Resolving Power	0.01 dB	
Linearity	± 0.2 dB	
OPM Connector	2.5 mm universal	
VFL Connector	2.5 mm universal	
VFL Output (Optional)	1 mW or 10 mW, CW and Glint	
LED Light	SOS code output	
Automatic Power Off	If no operation in 10 minutes (can be disabled) If low battery.	
Battery Charge	Yes	
Battery Life	Above 60 hours (OPM)	
Size	105 mm x 52 mm x 24mm	
Weight	About 100g	
Storage Temperature	-20 ~ +60 °C	
Operating Temperature	-10 ~ +50 °C	
Humidity	<90%RH	
Elevation	0 ~ 5000 m	
LED Light		

#### Accessories

OHOP6000-A1	Visual Fault Locator
-------------	----------------------